

# Invertec® V275-S

## For Stick and DC TIG Welding

The V275-S power source is ideal for the rigors of the construction site. IP23S rated and equipped with weather resistant features, this Stick and TIG power source is designed for outdoor use. Up to 275 amps of output gives you access to a greater number of stick electrodes, and outstanding 6010 performance. The V275-S is available as a single unit or mounted in 4-pack or 8-pack racks for convenience on the construction site. Standard features such as selectable Hot Start and adjustable Arc Force provide a level of arc control you won't find anywhere else in this class of machine.



### Processes

Stick    TIG    Gouging

### Advantage Lincoln

- Truly outstanding E6010 and E7018 performance using up to 7/32" diameter electrodes that enables both whip and drag techniques for a variety of construction and fabrication applications.
- Touch-Start TIG™ design permits the DC TIG welding arc to be established without high frequency starting.
- Air Carbon Arc cutting and gouging with up to 3/16" (4.8mm) diameter carbon electrode.
- Adjustable Arc Force and a two-position Hot Start switch provide a level of arc control you won't find in comparable machines.
- 25 more amps than competitor models provides access to a greater number of stick electrode types, diameters, and applications.
- No de-rating on single phase as with competitive models – get the same performance using single or three phase input.
- Only power source in its class that meets IP23S environmental rating.
- Aluminum chassis, protective boots on switches and potted and trayed PC boards for extreme environmental protection.
- Three-year warranty on parts and labor.
- Manufactured under a quality system certified to ISO 9001 requirements.

### Description

Output    Input

### Recommended General Options

Twist-Mate Cable Plug, Twist-Mate Cable Receptacle

### Recommended Stick Options

Accessory Kit, Remote Output Control

### Recommended TIG Options

17V Air-Cooled TIG-Mate™ Starter Pack, Twist-Mate Torch Adapter, Foot Amptrol™, Hand Amptrol

### Order

- K2269-1 Invertec V275-S
- K2269-2 V275-S (Rack Model)
- K2199-1 V275-S 4-pack Inverter Rack
- K2199-2 V275-S 8-pack Inverter Rack

### TECHNICAL SPECIFICATIONS


Product Name	Product Number	Input Power	Rated Output Current/Voltage/Duty Cycle	Input Current @ Rated Output	Output Range	Dimensions H x W x D inches (mm)	Net Weight lbs (kg)
Invertec V275-S	K2269-1	208/230/460/575/3/60	275A/31V/35% 250A/30V/60% 200A/28V/100%	38/37/19/16 34/33/17/14 27/25/13/11	5-275A	13.6 x 9.0 x 20.25 (345 x 229 x 514)	54.5 (24.7)
		208/230/460/575/1/60	275A/29-31V/35% 250A/30V/60% 200A/28V/100%	68/67/38/31 63/62/33/27 49/48/26/21			
		220/380/400/415/440/3/50	250A/30V/35% 200A/28V/100%	32/20/19/18/17 25/15/15/14/13			
		220/380/400/415/440/1/50	250A/30V/35% 200A/28V/100%	63/42/40/38/36 48/32/30/29/27			

## A CLOSER LOOK

### PERFORMANCE

- Truly outstanding E6010 and E7018 performance that enables both whip and drag techniques for a variety of construction and fabrication applications.
- Selectable Hot Start – Turn it off for thin material or flip it on to get the extra starting amperage you need for thick, rusty or dirty material.
- Variable Arc Force – Dial in the “soft” or “crisp” arc you want as conditions require. A crisper arc can be used to increase penetration or reduce electrode sticking on some applications.
- Touch-Start TIG™ design permits the TIG welding arc to be established without high frequency starting.

### ARC FORCE CONTROL



### FEATURES

- Full-featured MS-style remote capabilities – variable output control using a remote control device such as a foot pedal or hand control.
- 208/230/400/460/575 input volt settings – all-in-one machine. No need to buy separate models for added voltage.
- No single phase de-rating.
- Easy access reconnect panel – two quarter-turn captive screws. No need to remove several panels or machine case to switch input voltages.
- 25 more amps than competitor models provides access to a greater number of stick electrode types, diameters and applications.
- Recessed Control Panel – Provides optimal operating angle and helps protect controls from damage.



### QUALITY AND RELIABILITY

- Aluminum chassis for durability and corrosion resistance.
- Protective boots on switches for outdoor use.
- Potted and trayed PC Boards – encapsulated and protective trays provide best-in-class environmental protection.
- Fan-as-needed™ (F.A.N.) minimizes thermal cycling of internal machine components, minimizes internal contamination when not welding, and saves on electricity costs.
- Three-year warranty on parts and labor.
- Manufactured under a quality system certified to ISO 9001 requirements.



Potted and Trayed PC Board

### WHAT'S INCLUDED

#### K2269-1, V275-S Includes:

- V275-S
- Input Power Cable, 10 ft.
- Twist-Mate Cable Plugs (K852-70), quantity 2

#### K2199-1, V275-S 4-Pack Inverter Rack Includes:

- V275-S Rack Model power sources (K2269-2), quantity 4
- Inverter Rack

#### K2199-2, V275-S 8-Pack Inverter Rack Includes:

- V275-S Rack Model power sources (K2269-2), quantity 8
- Inverter Rack
  - An ideal system to group several inverter power sources in an industrial portable package. Entire system meets National Electrical Code (NEC) standards.
  - Includes V275-S rack model power sources. This special rack version has all the same features as the standard V275-S. Standard power cord is replaced by individual stranded wires in liquid tight conduit to meet NEC standards.



K2199-1, V275-S  
4-Pack Inverter Rack



K2199-2, V275-S  
8-Pack Inverter Rack

**GENERAL OPTIONS**



**Twist-Mate Cable Plug**  
For connecting welding cable to output terminal receptacles. For 1/0-2/0 (50-70mm<sup>2</sup>) cable.  
**Order K852-70**



**Twist-Mate Cable Plug**  
For connecting welding cable to output terminal receptacles. For 2/0-3/0 (70-95mm<sup>2</sup>) cable.  
**Order K852-95**



**Twist-Mate Cable Receptacle**  
For connecting welding cable to Twist-Mate cable plug. For 1/0-2/0 (50-70mm<sup>2</sup>) cable.  
**Order K1759-70**



**Twist-Mate Cable Receptacle**  
For connecting welding cable to Twist-Mate cable plug. For 2/0-3/0 (70-95mm<sup>2</sup>) cable.  
**Order K1759-95**

**STICK OPTIONS**



**Accessory Kit**  
For stick welding. Includes 35 ft. (10.7m) 2/0 electrode cable with lug, 30 ft. (9.1m) 2/0 work cable with lugs, headshield, filter plate, cover plate, work clamp and electrode holder. 400 amp capacity.  
**Order K704**



**Accessory Kit**  
For stick welding. Includes 20 ft. (6.1m) #6 electrode cable with lug, 15 ft. (4.6m) #6 work cable with lugs, headshield, work clamp, electrode holder and sample pack of mild steel electrode. 150 amp capacity.  
**Order K875**



**Remote Output Control**  
Consists of a control box with choice of two cable lengths. Permits remote adjustment of output. 6 pin connection.  
**Order K857** for 25 ft. (7.6m) or **K857-1** for 100 ft. (30.5m)

**TIG OPTIONS**



**17V Air-Cooled TIG-Mate™ Starter Pack**  
Get everything you need for TIG welding in one complete easy-to-order kit packaged in its own portable carrying case. Includes: PTA-17V Ultra-Flex™ torch, parts kit, Harris flowmeter/regulator, 10 ft. gas hose, and work clamp and cable. **Order K2265-1**



**Twist-Mate Torch Adapter**  
For connection of PTA-9 or PTA-17V torches (1 piece cable) to power sources without gas passing through the Twist-Mate connection.  
**Order K960-1**



**Foot Amptrol™**  
Provides 25 ft. (7.6m) of remote output control for TIG welding (6 pin plug connection).  
**Order K870**



**Hand Amptrol**  
Provides 25 ft. (7.6m) of remote current control for TIG welding. (6 pin plug connection). Velcro straps secure torch.  
**Order K963-13** (One size fits all Pro-Torch TIG Torches.)

**INVERTEC V275-S ORDER FORM**

PRODUCT DESCRIPTION	ORDER NUMBER	QUANTITY	PRICE
<b>INVERTEC V275-S</b>	<b>K2269-1</b>		
<b>V275-S 4-Pack Inverter Rack</b> - includes 4 Invertec V275-S power sources	<b>K2199-1</b>		
<b>V275-S 8-Pack Inverter Rack</b> - includes 8 Invertec V275-S power sources	<b>K2199-2</b>		
<b>RECOMMENDED GENERAL OPTIONS</b>			
Twist-Mate Cable Plug - 1/0 - 2/0 (50-70mm <sup>2</sup> ) Cable	K852-70		
- 2/0 - 3/0 (70-95mm <sup>2</sup> ) Cable	K852-95		
Twist-Mate Cable Receptacle - 1/0 - 2/0 (50-70mm <sup>2</sup> ) Cable	K1759-70		
- 2/0 - 3/0 (70-95mm <sup>2</sup> ) Cable	K1759-95		
<b>RECOMMENDED STICK OPTIONS</b>			
Accessory Kit (400 amps)	K704		
Accessory Kit (200 amps)	K875		
Remote Output Control - 25 ft. (7.6m)	K857		
- 100 ft (30.5m)	K857-1		
<b>RECOMMENDED TIG OPTIONS</b>			
17V Air-Cooled TIG-Mate™ Starter Pack	K2265-1		
Twist-Mate Torch Adapter	K960-1		
Foot Amptrol™	K870		
Hand Amptrol - For Smaller Handle 9, 17 or 20 Series Torches	K963-1		
	<b>TOTAL:</b>		

**CUSTOMER ASSISTANCE POLICY**

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for advice or information about their use of our products. We respond to our customers based on the best information in our possession at that time. Lincoln Electric is not in a position to warrant or guarantee such advice, and assumes no liability, with respect to such information or advice. We expressly disclaim any warranty of any kind, including any warranty of fitness for any customer's particular purpose, with respect to such information or advice. As a matter of practical consideration, we also cannot assume any responsibility for updating or correcting any such information or advice once it has been given, nor does the provision of information or advice create, expand or alter any warranty with respect to the sale of our products.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to [www.lincolnelectric.com](http://www.lincolnelectric.com) for any updated information.



**THE LINCOLN ELECTRIC COMPANY**

22801 St. Clair Ave., Cleveland, OH 44117-1199 • 216.481.8100 • [www.lincolnelectric.com](http://www.lincolnelectric.com)